



# Specification Sheet

## PS-1020

### Acid Activated, Low Odor, Paint Stripper

**PS-1020** is a high performance, viscous, acid-activated, non-phenolic paint remover, particularly effective for removal of polyurethane and epoxy paints from aircraft surfaces.

- Effective for removal of polyurethane and epoxy paints.
- Nonflammable.
- Low odor.

Spray or brush **PS-1020** onto surface to be stripped. Allow 20 minutes to 1 hour for paint to be loosened; agitate to break remaining bond, then rinse with stream of water. Upon completion of paint removal, use an alkaline soap, such as **AC-2010** to insure neutralization of the acidic product.

The use of litmus or pH paper should be used to confirm neutralization

Adequate ventilation is required, due to presence of chlorinated solvents.

Beware of pressure buildup in closed containers.

**Note:** Avoid contaminating **PS-1020** with water. **PS-1020** may cause pitting of aluminum when contaminated with water. **DO NOT** use on magnesium or high-strength steel.

**PS-1020** is an acid-activated product and is corrosive to skin and eyes. **PS-1020** should always be used with adequate ventilation and proper safety equipment, including full face shield, rubber apron, boots, and gloves. If any skin contact occurs, flush with water for 15 minutes, then wash with soap and water. If eyes are exposed, flush with water and seek medical attention.

#### Caution:

Avoid contact with skin and eyes. Use rubber clothing and face shield. Use with adequate ventilation. In case of accidental contact with eyes, flush with plenty of water, and contact physician.

#### Health Precautions:

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical, environmental hazards, handling precautions, and first aid recommendations. An SDS is available on request. Avoid overexposure. Seek medical attention in case of extreme overexposure.

**For Industrial Use Only.  
Keep away from children.**



# Specification Sheet

Approved by or Conforms to the following specifications:

---

Douglas CSD #1 "Aircraft Maintenance Chemicals"

- AMS 1376 Remover, Epoxy Paint Acid-Type, Thickened

All recommendations, statements, and technical data contained herein are based on tests Aero Clean Technologies, LLC believe to be reliable and correct. Accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. Users shall rely on their own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Aero Clean Technologies, LLC and Seller's sole responsibility shall be to replace only that portion of the product of Aero Clean Technologies, LLC which proves to be defective. Neither seller nor Aero Clean Technologies, LLC shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of Aero Clean Technologies, LLC shall not be binding upon the Aero Clean Technologies, LLC or seller.

Revision: 0001

Date: 6/28/2014